


SP-MDU-250

White and Opaque BOPP, both sides matt.



FEATURES

- High moisture, chemicals oil, and scratching resistance
- High mechanical strength, good dimensional stability
- Can be applied as indoor advertisement including POP, POS, banner etc.
- Good durability
- Stable Dyne level
- Very high yield
- Suitable for gravure, UV/offset, UV/flexo, UV inkjet, thermal transfer and screen printing etc

STANDARD ROLL SIZE AVAILABILITY

Film	Standard length (meters)		
	750mm	850mm	890mm
SP-MDU-250	750mm	850mm	890mm
Outside Diameter for Core 76mm	1700	2200	2400
Outside Diameter for Core 152mm	1600	2100	2300

Note: Other roll sizes are available subject to negotiation.
Various sheet samples are available on request.

TECHNICAL DATA (typical value)

Application		Bopp Film	
Product code		SP-MDU-250	
Appearance		Both sides matt	
Thickness (µm)		250	ISO 4593:1993
Density (g/cm ³)		0.64	Internal Measure
Weight (g/m ²)		160.0	Internal Measure
Yield (m ² /kg)		6.3	Internal Measure
Opacity (%)		97.0	ASTM D 1003-61
Gloss (%)	Front	14.0	ASTM 2457
	Back	14.0	
Whiteness (%)	Front	95.0	ISO 11476:2000
	Back	95.0	
Surface Tension (dyne/cm)	Front	≥41	ASTM D -2578
	Back	≥41	
Roughness (µm)	Front	1.756	ISO 4287
	Back	1.472	
Tensile strength (Mpa)	MD	40.0	ASTM D -882
	TD	95.0	

* Experimental data, only for reference.

FILM STORAGE

For the storage of Lichang BOPP film, it is recommended that dry conditions at temperatures below 30° to minimize the deterioration of the film properties in general. The film is suitable for use up to 6 months from the date of production.

Quanzhou Lichang Plastics Co. Ltd.

www.lichangplastic.com

Manufacture: Fuxian Industry Zone, Shuitou Town, Nan'an City, Fujian Province, China, 362342

Head Office Tel: +86 0595-86997773; +86 0595-86997757

Overseas Marketing Department Tel: +86 0592-5023518

This figures and data provided in this datasheet are consistent with the current state of our knowledge and are intended to provide average or typical values about our products and their applications. Use of this information is limited to the specific recipient. The user is solely responsible for all determinations regarding use and we disclaim liability for any loss or damage that may occur from the use of this information.

Certified according to ISO 9001. Lichang BOPP films do not present any significant danger to health and safety in the workplace.

Edition: APR 2019