


# <u>SP-PN</u>

White and opaque BOPP, both sides glossy.



#### **FEATURES**

- High moisture, chemicals oil, and scratching resistance
- Recyclable with polyolefin materials
- High mechanical strength, good dimensional stability
- Good durability
- Excellent die-cutting
- Suitable for gravure, flexographic printing (water based ink)

#### **STANDARD ROLL SIZE AVAILABILITY**

Film	Standard length (meters)				
SP-PN	750mm	850mm	890mm		
Outside Diameter for Core 76mm					
Outside Diameter for Core 152mm					
<b>Note:</b> Other roll sizes are available subject to negotiation. Various sheet samples are available on request.					

## **TECHNICAL DATA (typical value)**

Арр	lication		Bopp Film			
Produc	ct code	SP-PN				
Арреа	arance		Both sides glossy			
Thickne	ess (µm)	75	100	120		
Density	(g/cm <sup>3</sup> )	0.60	0.60	0.60		
Weight	: (g/m²)	45.0	60.0	72.0		
Yield (	m²/kg)	22.2	16.7	16.7		
Opaci	ty (%)	85.0	90.0	92.0		
Gloss (%)	Glossy	94.0	96.0	98.0		
	Matt	94.0	96.0	98.0		
Whiteness	Glossy	80.0	80.0	80.0		
(%)	Matt	80.0	80.0	80.0		
Surface	Glossy	≥39	≥39	≥39		
Tension (dyne/cm)	Matt	≥39	≥39	≥39		
Roughness	Glossy	0.080	0.080	0.080		
(µm)	Matt	0.090	0.090	0.090		
Tensile strength	MD	40.0	40.0	40.0		
(Mpa)	TD	95.0	95.0	95.0		

\* Experimental data, only for reference.

### FILM STORAGE

For the storage of Lichang BOPP film, it is recommended that dry conditions at temperatures below 30° to minimize the deterioration of the film properties in general. The film is suitable for use up to 6 months from the date of production.

Quanzhou Lichang Plastics Co. Ltd. www.lichangplastic.com Manufacture: Fuxian Industry Zone, Shuitou Town, Nan'an City, Fujian Province, China, 362342 Head Office Tel: +86 0595-86997773; +86 0595-86997757 Overseas Marketing Department Tel: +86 0592-5023518

This figures and data provided in this datasheet are consistent with the current state of our knowledge and are intended to provide average or typical values about our products and their applications. Use of this information is limited to the specific recipient. The user is solely responsible for all determinations regarding use and we disclaim liability for any loss or damage that may occur from the use of this information.

Certified according to ISO 9001. Lichang BOPP films do not present any significant danger to health and safety in the workplace.